

Astoria™

Two-piece Round Toilet UR201125WH



Features

- Vitreous China
- Boxed rim, jetted bowl
- 12” (305 mm) rough-in
- 1.28 gpf/4.8 Lpf
- Includes color matched plastic trip lever
- Sanitary bar on all bowls
- Toilet seat sold separately
- Limited Lifetime Warranty

Model

UR201125WH Combination:
UR2011WH Astoria Round front bowl

UR2025WH Astoria 12” Rough-in tank & lid

Total Shipping weight: 78 lbs (35 kg)

UR2011WH shipping weight: 47 lbs (21 kg)

UR2025WH shipping weight: 31 lbs (14 kg)

Alternate Tanks:

- UR2026WH Astoria 12” Rough-in, 1.28 gpf tank, RH trip lever
- UR2027WH Astoria 10” Rough-in, 1.28 gpf tank, LH trip lever
- UR2028WH Astoria 14” Rough-in, 1.28 gpf tank, LH trip lever
- UR2021WH Astoria 12” Rough-in, 1.6 gpf tank, LH trip lever

Colors

☐ White (130)



Codes & Standards

Meets or exceeds the following:

- ASME A112.19.2
- CSA B45.1
- IAPMO/cUPC




Astoria™

Two-piece Round Toilet UR201125WH



Specifications



UR201125WH			
A	Overall from wall: 28 1/8" (713) Product only: 27 1/8" (689)	B 16 1/2" (419)	C 14 3/4" (375) D 29" (737)

Material	Ceramic
Rough-In	12" (305mm)
Water Usage	1.28 gpf
Water Pressure Range	20/50/80 PSI
Flush System	2" Single Flush
Water Surface Area	≥ 125 * 100 mm
Trap Diameter	≥ 1 7/8"

Trap Seal	≥ 51 mm
Shipping Weight	78 lbs (35 kg)
Warranty	Ceramic: Lifetime Tank fittings: 1 year

Dimensions may vary (+) or (-) 1/4". Dimensions shown in parentheses are in millimeters: 25.4 mm = 1 inch. Note: Fixture dimensions are nominal and conform with dimension and performance requirements of ASME A112.19.2/CSA B45.1 standards. PSI rating: 20 minimum to 80 maximum per ASME A112.19.2/CSA B45.1 standards. Dimensions subject to change or cancellation without notice. Universal Rundle is not responsible for the use of superceded or voided specification information. Universal Rundle reserves the right to make revisions without notice to product specifications. For the most current Specification Sheet, visit www.universalrundle.com